

R-13

# OREGON PUBLIC LAND CORNER REPORT / RESTORATION REPORT

## MORROW COUNTY SURVEYOR'S OFFICE

<b>SECTION</b> 27	<b>TOWNSHIP</b> 4 S.	<b>RANGE</b> 25 E.	
<b>MORROW COUNTY</b>		<b>DATE</b> June, 2012	
<b>CORNER DESIGNATION:</b>			
(Please check one)			
<input type="checkbox"/> Condition Report Only			
<input type="checkbox"/> Not Found			
<input checked="" type="checkbox"/> Renewed			
<input type="checkbox"/> Unrecorded			
<input type="checkbox"/> Surveyed In			
<input type="checkbox"/> Referenced Out			
<b>4S25R13</b>			
<i>Previous Renewals / Surveys. etc.</i>			
Originally set by Zenas F Moody under contract No. 184, dated March 29, 1873. He set a stone 15x12x10 for the corner to Sections 27, 28, 21 and 22.			
<b>Monument(s) &amp; Accessories Found: (Condition &amp; Source)</b>			
Found a stone of record size in the center of a mound of stone.			
<b>Monument Detail:</b>	<div style="text-align: center;"> </div>		
<b>Monument Set (Procedures and Description):</b>			
Set 1"x36" galvanized iron pipe with a 2-1/2" Brass Cap stamped as shown above, 20" in the ground and raised a mound of stone around it.			
<b>New Accessories:</b>			
Set four 5/8"x20" iron rods with 2" Aluminum Caps stamped Oregon Dept. of Transportation. The monument and references were ties using Leica System 1200 RTK GPS. Bearings and distances to corner as follows: RP1 - N43-58'E, 14.60 Feet, RP2 - S44-55'E, 14.32 Feet, RP3 - S41-45'W, 14.46 Feet, RP4 - N42-11'W, 16.08 Feet			
<b>Location &amp; Comments:</b>		<b>Compass Declination:</b>	
<b>Firm / Agency</b>		<b>SURVEYOR'S SEAL</b>	
Oregon Department of Transportation, Geomtronics Unit		<div style="border: 1px solid black; padding: 5px; display: inline-block;">             REGISTERED PROFESSIONAL LAND SURVEYOR           </div>	
<b>Party Chief</b>			
J. David Brinton, PLS		<div style="border: 1px solid black; padding: 5px; display: inline-block;">             OREGON December 2, 1983 J. David Brinton 2065           </div>	
<b>Notes</b>		<b>RENEWAL DATE:</b> 12/31/13	
<b>Witness</b>			
Bill Dye, PLS			