

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. N-5

History of original corner establishment:

DIAGRAM

This corner was originally established by Edward W. Sanderson in 1881-82 under GLO Contract Number 471. Surveyor General Field Notes state:

T55 R27E
S18 S17

Set sandstone 21x10x5 ins. 14 ins. in the ground for cor to Secs 17,18,19 and 20 Marked with 3 notches on S and 5 notches East edges from which

S19 S20
1992
PLS 848

A Pine 20 ins. dia. bears N35°E, 32 lks. dist marked	T5S R27E	Sec 17	BT
A Pine 18 ins. dia. bears N35°W, 45 lks. dist marked	T5S R27E	Sec 18	BT
A Pine 24 ins. dia. bears S20°W, 42 lks. dist marked	T5S R27E	Sec 19	BT
A Pine 8 ins. dia. bears S80°E, 39 lks. dist marked	5S R27E	Sec 20	BT

Description of Corner Evidence Found:

None found. Stone has been lost to logging

Rotten Ponderosa Pine stump, with scribe BT visible, bears N63°24'W, 29.26 ft. (Record: N55°W, 29.7 ft)

Ponderosa Pine, 28" dia, with scribe "R27ES" visible, bears N26°21'E, 9.18 ft. (Record: N35°E, 21.12 ft)

Ponderosa Pine snag, 10" dia, with healed blaze, bears S80°09'E, 26.63 ft. (Record: S80°E, 25.74 ft.)

Ponderosa Pine, high stumped with scribes "R27E S19 BT" visible, bears S19°51'W, 28.31 ft. (Record: S20°W, 27.72 ft.)

These reported bearing are based on the best fit from the physical location of the bearing trees and the record. When the record was applied to the bearing trees there was quite a discrepancy in corner location between the northeast and northwest bearing trees. The corner location was determined by extending the bearings of the southeast and southwest bearing trees to the point of intersection with each other.

Description of monument and accessories I established to perpetuate the original location of this corner:

Based on the best fit from above recovered bearing trees I set 2- 1/2"x30" aluminum pipe with 3-1/2" aluminum cap, stamped as shown on the DIAGRAM, 26 " in the ground.

From which:

Douglas Fir, 8" dia., bears N45°30'W, 111.4 ft., scribed:	T5S R27E	S18	BT
Douglas Fir, 16" dia., bears N49°45'E, 31.7 ft., scribed:	T5S R27E	S17	BT
Douglas Fir, 16" dia., bears S52°45'E, 12.8 ft., scribed:	T5S R27E	S20	BT
Pond. Pine, 10" dia., bears S25°30'W, 111.9 ft., scribed:	T5S R27E	S19	BT

Measurements to BT's taken with a magnetic compass, declination 20° East, and a nylon clad steel tape. Set steel fence post with Land Survey Monument (54-9) sign 5' north of the monument. Nailed a brass washer stamped PLS 848 on blaze above BT scribe as taken this survey. Nailed Bearing Tree (54-3) signs above blaze and Land Survey Monument (54-9) sign on back of each tree as required. Painted a 6" red band above Bearing Trees signs and painted blaze red.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 12 1898
DOUGLAS M. FERGUSON
848

This work was performed by:
Douglas M. Ferguson PLS 848
Witnessed by: D. Mitchell Ferguson
and Rick Saul
March 26, 1992
Refer to Morrow Co. Survey No.: C-936-E

Office of OR I hereby certify that the within instrument was filed in this office for record on the 9 day of July, 1992
County of MORROW
by SR
(COUNTY OFFICIAL) (DEPUTY)