

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

DIAGRAM BY ORIGINAL SURVEY RECORDED(SHEET):

INDEX: 0-15

DEPTER QUARTER CORNER SECTION 3, T.55, R.25E., W.M.

1	DIAGRAM	
1		
1	755 202E	
1		
1	01/4 , 82	
1		
1	1979	
1	PLS 1638	
1		
1		

DESCRIPTION OF CORNER EVIDENCE FOUND:
 FOUND THE 1/4 CORNER AS DESCRIBED WITH CROSS BAR DEMONED AS SHOWN IN THE
 DIAGRAM FROM WHICH:
 A BESS AND DOWN 10' DBH LODGEPOLE PINE BEARS N65°02'15" 10.0' WITH
 VISIBLE SCIDE:
 A BESS AND DOWN 10' DBH LODGEPOLE PINE BEARS 88°1'01" 12.0' WITH
 VISIBLE SCIDE.

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO DEMONSTRATE THE
 ORIGINAL LOCATION OF THIS CORNER:
 THE BEARING WERE BASED ON THE SURVEYED BEARING BETWEEN THE 1/4 WITNESS
 CORNER AND THE N 1/4 CORNER OF SECTIONS 3 AND 4 AS RECORDED BY PLS 1008
 IN MONTGOMERY COUNTY SURVEY 265-K. I SET THE FOLLOWING NEW WITNESS TREES:
 A 14' DBH ENGLISHAN SPRUCE BEARS 88°02'15" 02'15" 81.4' SCYLED 01/4538T1
 A 6" DBH DOUGLASS FIR BEARS N22°53'15" 31.5' SCYLED 01/4538T1
 A 6" DBH LOGSPOLE PINE BEARS 88°1'02'15" 24'15" 57.2' SCYLED 01/4538T1
 A 10' DBH REDBERRY LARIX BEARS 82°58'15" 74.7' SCYLED 01/4538T1
 AN ALUMINUM WASHER BEARING PLS 852 IS NAILLED BETWEEN THE TREES B AND T
 ON THE NEW BESS. ALL THE 3TIE TAVE 12M AND 3T BEARS 4540T25.
 BEARING 80' VER BANNER AROUND ALL THE TREES AND DAIRED THE
 SCYLED BEARS WED.

THIS WORK WAS DONE OCTOBER 29, 1952.

**REGISTERED
 PROFESSIONAL
 LAND SURVEYOR**

David L. Haddock

**OREGON
 JULY 12, 1958
 DAVID L. HADDOCK
 852**

Office of _____ County of _____
 DEPTER OF _____ I HEREBY CERTIFY THAT THE WITHIN INSTRUMENT WAS FILED
 IN THIS OFFICE FOR RECORD ON THE _____ DAY OF _____, 19____
 BY _____ (DEPUTY)

FORM 36-7130-57 (9/71)