CERTIFIED RECORD OF LAND CORNER MONUMENTATION T6S, R25E

2-15½

History of original corner establishment:

This monument was marked in 1879 by A. York under G.L.O contract No. 309. He described it as a Pine, 36" dia. It was found in 1881 by E.W. Sanderson during his retracement under G.L.O. contract No. 368. He described it as a Pine on line 24" dia., and found it to be 1.00 chain West of the corner to Secs. 34 and 35 set by him.

DIAGRAM

T6S R25E
S34

LINE TREE

S2
T7S R25E

Description of corner evidence found:

I found a dead P. Pine, 42" dia., with axe work on East and West sides. This tree lies 62.5 feet westerly from the corner to Secs. 34 and 35 recovered by Kurt Weaver, L.S. 1679, in his survey of 1980.

Description of monument and accessories I established to perpetuate the original location of this corner:

I added an "attention" sign and a 6" red enamel stripe to the line tree from which:

White Fir, 24" dia., bears N32 3/4°W, 18.6 ft.
Scribed: "AP S34 BT"

Douglas Fir, 18" dia., bears S38¼°W, 43.6 ft.
Scribed: "AP S2 BT"

The B.T.'s have an "attemtion" sign, a B.T. tag, a 6" red enamel stripe and an alum. "PLS 1832" washer.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

Fayette S Munro

OREGON
JULY 13, 1979
FAYETTE S. MUNRO
1832

RECEIVED BY
Morrow County Surveyor
Date 10/24/84
Rec'd by M.W.D.
No. ~~682~~-K
702

Office of Surveyor County of Morrow Co.
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 2 day of July, 1984
David H. Klein by
(COUNTY OFFICIAL) (DEPUTY)

Form R6-7100-57 (9/71) GPO—798-576