

27 26 1/4 SECTION CORNER
2" IRON PIPE

FND 3/4" IRON PIPE 200.00
0.53
0.5 W
N 89° 46' 00" E 452.00
252.00
1/2" IRON PIN

2.00 ACRES
CROOK TRACT

384.30
S 08° 12' 28" E

N 00° 14' 00" W
1212.61

N 00° 14' 00" W
584.00

260.00
S 89° 46' 00" W

41.78
N 00° 14' 00" W

5.23 ACRES

FND 3/4" IRON PIPE
0.4 E
0.53
N 89° 46' 00" E 175.00

FND 3/4" IRON PIPE
0.00 N
0.00 E

R CURVE DATA
R = 75.77
C = 83.46
C & N 83° 03' 10" E
A = 60° 50' 20" W
L = 88.39

N 24° 38' 00" E 171.03

20' ROAD EASEMENT

S 88° 31' 40" E
263.00

N 89° 31' 40" W
587.04
627.28

FND 3/4" IRON PIPE 40.24
1/2" IRON PIN

NOTE:
DEPARTS FROM "RIVERSIDE"
ADDITIONAL TO HEREIN

LEGEND
• DENOTES POINTS FOUND
o DENOTES POINTS SET



27-4-51
John Harris Co. Inc.
Pendleton, Oregon
By [Signature]

N 00° 14' 00" W
1321.25
27 26
34 35
FND AXLE

SURVEY FOR		WAYNE HARRIS CO INC			
NORMAN PAULLUS, SITUATED IN		ENGINEERS-SURVEYORS PENDLETON, OREGON			
THE SW 1/4 SEC 26, T 2S, R 26E, WM, MORROW CO, OR.		SCALE	1" = 60'	DRN BY	JKM
		DATE	9-26-75	CKD BY	CTP
					DRNG NO 75-96B