

Arthur Reid - Survey.

Go to the $\frac{1}{4}$ corner on N. side sec. 13 T₁S., R. 26 E. Thence south 20 ch. Drove temp stk. 40 ch. Drove temp stk. 46 ch. intersect county road to Parker's Mill 80.24 ch. intersect E+W. line 66 lks W. of corner. The corrections for each quarter mile is therefore S. 6 lks. and E. $16\frac{1}{2}$ lks.

Set rock 12x10x6 at S.E. cor N.E. $\frac{1}{4}$ S.W. $\frac{1}{4}$ Sec 13 from which Bull Pine 4 in. diam. bears N. 59° W. 28 lks. Bull Pine 5 in. diam. S. 59° W. 25 lks.

Set rock 30x10x5 for N.W. cor S.E. $\frac{1}{4}$ Sec. 13 from which Bull Pine 18 in.

diam. bears N. $78^{\circ}-30'$ E. 71 lks. Bull Pine 10 in. diam. S $86^{\circ}-E$. 28 lks.

South from the $\frac{1}{4}$ corner between secs. 13 & 14 T₁S, R, 26 E. 20 ch. set temp. stk. 40.72 intersect E. & W. line 38 lks E. of corner. The corrections therefore are for the quarter mile 36 lks South and 19 lks West. Set rock 16x10x8 for corner from which Red fir 10 in. diam. bears West 8 lks. White Fir 8 in. diam. S. $75^{\circ}E$. $30\frac{1}{2}$ lks. White Fir. 6 in. N. $80^{\circ}E$. 10 lks.

Thence East across Sec. 13. Intersect N. & S. line through center $36\frac{1}{2}$ lks. N. of center by measurement and intersect N & S. section line 1.42 ch N. of $\frac{1}{4}$ corner.

May 27 + 28 - 1909.

D. V. J. Reid - County Surveyor.