

Mar. 20, 1925

Survey in Sec 27

D. R. S. P. 27, E. W. M.

Flag corner to Sec 20

21-22-27-28.

Set upon 1/4 cor bet

Secs 27 & 34, D. R. S. P. 27 & 28.

Run Random Line West

20.00 set temp 1/4 cor bet

40.00 set temp cor 7 Sec 20

22-28-32-34.

5-1/2 mls West of fence

35/1/2 mls North of fence corner.

Jim Morgan } Chainmen
Tom Beynner }
Guy Boyer }
Flagman

More corner 1/2 mls South Set stone 8/20

Weld 1/2 mls North CS on south face

Mon corner South 8/1/2 mls

Direct in Line and Halfway between

Sec corners North & South one 1/2

Line East bears N. 89° 32' E

Line West to sec Cor bears N. 89° 45' W.

Run Random line = South
from cor to Sess. 27-28-33-34

TRSR 27 E

0.35 fence corners

2.38 Mound of Rock

40.00 set temp speed.

61.00 North Bank of Willow Creek

80.98 To Cor to Sess 33-34-35-4

Apr 24 SSR 27 E

Go back to temp corner to

Sess. 27-28-30-34

and find its bed direct in line
between Section Corners
North & South.

85
Book 16

Set up on Temp Cor to
Sec 27-28-33 & 34
4x1111 ~~Line~~ Line direct
to Cor to Secs 21-22-27-28

Road set Temp 1/4 cor.

39.65 in Line with fence running
West find mound and traces
of Pits at this point.

Road set Temp 1/4 corner

60.40 South bank of Willow Creek

69.2506 to state edge of field.

12.03

79.2806 A

86
Book 16

80.92
79.28
160.20

Set Stone 57X 15 Mtd 1/6 CS on West side
Flag Line N. 89° 32' E